

**MADE BY
DERC**

Speed Regulated Pipe Cleaner - SPC

The DERC Speed Regulated Pipe Cleaner (SPC) is the ideal rotating nozzle for cleaning horizontal and vertical pipes with multiple elbows. The compact, stainless steel design ensures that this nozzle can unplug, polish or run longer lines.

The rotation speed can be easily adjusted using a spanner to set the SPC tool for each application. The SPC is designed and constructed for water-blast cleaning of pipes as small as 4" with elbows. The SPC Centralizer makes it possible to centre the pipe cleaner to protect the rotating nozzle and achieve the best cleaning results.

Features

- Pressures up to 3,000 bar
- Flow rates up to 210 lpm
- Horizontal and vertical pipes
- Low maintenance
- Short and robust design
- Long life of high pressure seals
- Various inlet connection options
- Heavy duty stainless steel construction



SPC-L



SPC-M



SPC-UH

CALDER



Speed Regulated Pipe Cleaner - SPC

SPC-L

	SPC-L	SPC-L
Pressure	1,000 bar	1,500 bar
Flow	55 - 210 lpm	50 - 170 lpm
Inlet connection	1/2" NPT F	M24 x 1.5 DKOS M36 x 2 DKOS
Rotation speed	50 - 300 rpm	50 - 300 rpm
Pipe	6" - 12"	6" - 12"

SPC-M

	SPC-M	SPC-M
Pressure	1,000 bar	1,500 bar
Flow	50 - 115 lpm	50 - 110 lpm
Inlet connection	3/8" NPT F	M24 x 1.5 DKOS M 3/4" type M
Rotation speed	100 - 300 rpm	100 - 300 rpm
Pipe	4" - 6"	4" - 6"

SPC-UH

	SPC-UH-H6-R4	SPC-UH-H6F-R6	SPC-UH-H6F-R8.5
Max. Pressure	3,000 bar	3,000 bar	3,000 bar
Flow - pressure 2,500 bar	35 - 55 lpm	25 - 35 lpm	17 - 25 lpm
Flow - pressure 2,800 bar	35 - 50 lpm	25 - 35 lpm	17 - 25 lpm
Flow - pressure 3,000 bar	35 - 50 lpm	25 - 35 lpm	17 - 25 lpm
Inlet connection	3/4"UNF F	3/4"UNF F	3/4"UNF F
Rotation speed	100 - 500 rpm	100 - 500 rpm	100 - 500 rpm
Pipe	4" - 8"	4" - 8"	4" - 8"

SPC-UH

	SPC-UH-78UHM-R4	SPC-UH-78UHM-R6	SPC-UH-78UHM-R8.5
Max. Pressure	3,000 bar	3,000 bar	3,000 bar
Flow - pressure 2,500 bar	35 - 55 lpm	25 - 35 lpm	17 - 25 lpm
Flow - pressure 2,800 bar	35 - 50 lpm	25 - 35 lpm	17 - 25 lpm
Flow - pressure 3,000 bar	35 - 50 lpm	25 - 35 lpm	17 - 25 lpm
Inlet connection	7/8"UNF M	7/8"UNF M	7/8"UNF M
Rotation speed	100 - 500 rpm	100 - 500 rpm	100 - 500 rpm
Pipe	4" - 8"	4" - 8"	4" - 8"

Made by Derc Salotec
and distributed by
Calder Limited
Prescott Drive
Worcester
WR4 9NE
United Kingdom

+44 1905 751790
sales@calder.co.uk

