

MultiJet

High Pressure Waterjetting



235 HP (170 kW), and 347 HP (260 kW) options

For over ten years, the HOEIT/Calder team have been supplying mobile waterjetting units to the Middle East region. During that time we have built up a well-trained team of local and European engineers who are there to provide support to our customers across the varied industries who use high pressure water.

The latest update to our range sees the introduction of two new models — the 140iV and 200iV. Both units feature the Hammelmann reciprocating plunger pump which has proved its reliability in the toughest of industries for many years. This pump's long time between services offers a huge advantage to the operator in terms of uptime and productivity.

Features of these units:

- on-board controls
- spark arrestor
- overspeed valve
- inlet water filter
- boost pump
- water tank
- integral fuel tank
- direct drive
- trailer or skid
- conversion kits
- local spares stock
- local service team



MultiJet 140iV

plunger dia (mm)	working pressure psi (bar)	flow rate usgpm (lpm)
20	40,610 (2,800)	7.1 (27)
25	26,106 (1,800)	11.0 (42)
28	20,740 (1,430)	14.0 (53)
30	17,984 (1,240)	16.1 (61)
33	14,935 (1,030)	19.8 (75)
35	13,198 (910)	22.1 (84)
40	9862 (680)	29.3 (111)



MultiJet 200iV



plunger dia (mm)	working pressure psi (bar)	flow rate usgpm (lpm)
20	40,610 (2,800)	10.8 (41)
25	25,381 (1,750)	16.3 (62)
28	20,305 (1,400)	20.6 (78)
30	17,404 (1,200)	22.9 (87)
33	14,935 (1,030)	29.0 (110)
35	12,763 (880)	31.7 (120)
40	10,007 (690)	41.7 (158)



P.O. Box 174, Al-Khobar 31952, Saudi Arabia
 Telephone: + (966) (13) 887-7390
 Fax: + (966) (13) 887-7830
 Email: info@hoeit.com

the very best in high pressure waterjetting technology