Speed Regulated Pipe Cleaner - SPC

The DERC Speed Regulated Pipe Cleaner (SPC) is the ideal rotating nozzle for cleaning horizontal and vertical pipes with multiple elbows. The compact, stainless steel design ensures that this nozzle can unplug, polish or run longer lines.

The rotation speed can be easily adjusted using a spanner to set the SPC tool for each application. The SPC is designed and constructed for waterblast cleaning of pipes as small as 2" with elbows. The SPC Centralizer makes it possible to centre the pipe cleaner to protect the rotating nozzle and achieve the best cleaning results.

Features

- For pipe sizes: 2" 4", 4" 6", 6" 12"
- Pressures up to 3,000 bar
- Flow rates up to 210 lpm
- Horizontal and vertical pipes
- Low maintenance
- Short and robust design
- Long life of high pressure seals
- Various inlet connection options
- Heavy duty stainless steel construction





SPC-S



SPC-M



SPC-L



SPC-UH



Speed Regulated Pipe Cleaner - SPC



SPC-S	SPC-S-14NF	SPC-S-14F	SPC-S-M9FR
Max. pressure	1,000 bar	1,500 bar	1,500 bar
Inlet connection	1/4"NPT F	1/4"BSP F	9/16"UNFRH
	SPC-S-M9FL	SPC-S-M6RF	SPC-S-M6LF
Max. pressure	SPC-S-M9FL 1,500 bar	SPC-S-M6RF 1,500 bar	SPC-S-M6LF 1,500 bar

All SPC-S models: Flow 30—55 lpm Rotation speed 100—300 rpm For pipe sizes 2" - 4"

SPC-L	SPC-L	SPC-L	
Max. pressure	1,000 bar	1,500 bar	
Flow	55 - 210 lpm	50 - 170 lpm	
Inlet connection	1/2" NPT F	M24 x 1.5 DKOS M36 x 2 DKOS	
Rotation speed	50 - 300 rpm 50 - 300 rpm		
For pipe sizes	6" - 12"	6" - 12"	

SPC-M	SPC-M	SPC-M	
Pressure	1,000 bar	1,500 bar	
Flow	50 - 115 lpm	50 - 110 lpm	
Inlet connection	3/8" NPT F	M24 x 1.5 DKOS M 3/4" type M	
Rotation speed	100 - 300 rpm 100 - 300 rpm		
For pipe sizes	4" - 6"	4" - 6"	

SPC-UH	SPC-UH-H6-R4	SPC-UH-H6F-R6	SPC-UH-H6F-R8.5	
Flow at 3,000 bar	35 - 50 lpm	25 - 35 lpm	17 - 25 lpm	
Inlet connection	3/4"UNF F	3/4"UNF F	3/4"UNF F	
	SPC-UH-78UHM-R4	SPC-UH-78UHM-R6	SPC-UH-78UHM-R8.5	
Flow at 3,000 bar	35 - 50 lpm	25 - 35 lpm	17 - 25 lpm	
Inlet connection	7/8"UNF M	7/8"UNF M	7/8"UNF M	
All SPC-UH models: Max. pressure 3,000 bar Rotation speed 100—500 rpm For pipe sizes 4" - 8"				

